

# SC-32-0110-0001-99

## SmartCell Red Sounder and Wall-Beacon (VAD Red Flash)

### Overview

---

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

---

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-32-0110-0001-99

## SmartCell Red Sounder and Wall-Beacon (VAD Red Flash)

### Technical specifications

---

#### General

---

Wireless frequency 868 MHz

---

#### Electrical

---

Batteries 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)

---

#### Sounder

---

Output level 95 dB(A) at 1 m max.

---

Output level adjustment High or low

---

Selectable tones 32

---

#### VAD

---

Colour Red flash

---

Rating W-3-5.11

---

Flash frequency 0.5 Hz (1 flash, every 2 seconds)

---

#### Physical

---

Physical dimensions 110 x 77 mm (Ø x D)

---

Net weight 0.2 kg

---

Colour Red

---

Mounting type Wall mount

---

Mounting position Wall

---

#### Environmental

---

Operating temperature -10 to +55°C

---

Storage temperature -10 to +30°C (with batteries)  
-10 to +55°C (without batteries)

---

Relative humidity 95% noncondensing max.

---

IP rating Type B: for indoor/outdoor use (IP33)

---

#### Regulatory

---

Compliance CE

---

Certification CPR

---

Standards EN54-3  
EN54-13  
EN54-23  
EN54-25

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 11 January 2024 - 12:44