

SC-32-0220-0001-99 SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-32-0220-0001-99 SmartCell White Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

General	
Wireless frequency	868 MHz
Electrical	
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride
	batteries (Fanso or Titus)
Sounder	
Output level	95 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32
VAD	
Colour	white flash
Rating	W-2.4-6
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
Physical	
Physical dimensions	110 x 77 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount
Mounting position	Wall
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)
	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
IP rating	Type B: for indoor/outdoor use (IP33)
Regulatory	
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-23 EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.