

SC-33-0110-0001-99

SmartCell Red Sounder and Ceiling-Beacon (VAD Red Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-33-0110-0001-99

SmartCell Red Sounder and Ceiling-Beacon (VAD Red Flash)

Technical specifications

General

Wireless frequency 868 MHz

Electrical

Batteries 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)

Sounder

Output level 92 dB(A) at 1 m max.

Output level adjustment High or low

Selectable tones 32

VAD

Colour Red flash

Rating Category C-3-9.5

Flash frequency 0.5 Hz (1 flash, every 2 seconds)

Physical

Physical dimensions 110 x 79 mm (Ø x D)

Net weight 0.2 kg

Colour Red

Mounting type Ceiling mount

Mounting position Ceiling

Environmental

Operating temperature -10 to +55°C

Storage temperature -10 to +30°C (with batteries)
-10 to +55°C (without batteries)

Relative humidity 95% noncondensing max.

IP rating Type B: for indoor/outdoor use (IP33)

Regulatory

Compliance CE

Certification CPR

Standards EN54-3
EN54-13
EN54-23
EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 11 January 2024 - 12:43