



DESTINATION

AWOH series of hermetic metal enclosures providing protection against external factors such as water (moisture) and dust (dirt). Appropriate edge design, a cast gasket on the door and metal lock(s) ensure an IP66 rating (IP protection rating).

Enclosure and door are made from 1.2mm thick sheet metal, the mounting plate from 1.5mm sheet metal. This ensures high resistance to mechanical damage - resistance class IK10 (degrees of mechanical strength IK).

Enclosures are protected against corrosion and finished with textured epoxy polyester grey paint - RAL7035 (grey structure). Their quality and aesthetically design make them perfectly siutable to modern residential, office and industrial buildings

TECHNICAL DATA	
External dimensions of enclosure	W=500, H=700, D=200 [+/-2 mm]
Mounting plate dimensions	W ₁ =450, H ₁ =665 [+/-2 mm]
Net/gross weight	16 / 16,9 [kg]
Destination	outdoor
Closing	2 x double-bit lock
Material	Enclosure and door - sheet, thickness: 1,2mm; mounting plate - sheet 1,5mm
	anticorrosion protection; Colour: RAL7035, grey, struktural
Degree of protection EN60529	IP66
Operating conditions	-10°C ÷ +40°C, Relative humidity 20%90%, without condensation
Declarations, warranty	CE, 2 years
Notes	changeable door – right or left







